

“CONID Cu” Electrowelded COPPER downpipe

Technical characteristics:	
Base Metal	Copper Cu-DHP
Reference standard	UNI EN 1172
Pipe tolerances - diameter and length	UNI EN 612 (excluding thickness 0.5 – 0.55 mm)
Markings	All pipes we produced are marked with: <ul style="list-style-type: none"> • Thickness • Diameter • Production standard
Use:	
Industrial and civil construction	

STANDARD PRODUCTION					
DIAMETERS MM	THICKNESSES				
	0.50 MM	0.55 MM	0.60 MM	0.70 MM	0.80 MM
Ø 60	2 MT	2 MT	1-2-3-4 MT		
Ø 75		2-3-4-5 MT			
Ø 76			2-3 MT	2 MT	
Ø 80	1-2-3-4-6 MT	3-4-6 MT	1-2-3-4-6 MT	2 MT	4 MT
Ø 87			1-2-3 MT	2 MT	
Ø 100	1-2-3-4-6 MT	2-3-4-5-6 MT	1-2-3-4-6 MT	2-3 MT	4 MT
Ø 120			1-2-3-4 MT	2-3 MT	4 MT
80X80	2-3-4 MT		2-3-4 MT	2 MT	
100X100			2-3-4 MT	2 MT	
60X90			3-4 MT		
OTHER THICKNESSES AND LENGTHS AVAILABLE ON REQUEST					