

## PREPAINTED ALUMINIUM VESTIS LINE

<b>Technical features:</b>	
Standard	UNI EN 485-2, UNI EN 573-3
Metal base	Alluminio 99,5%
Alloy type	Lega series 3000
Physical state	H44
Coating	<ul style="list-style-type: none"> <li>• Side A: coating, thickness 40 <math>\mu\text{m} \pm 5</math></li> <li>• Side B: primer + coating, thickness 12 <math>\mu\text{m}</math></li> </ul>
Standard colours	Roof patina green /Roof titanium grey / RAL7016 /RAL9006 /Testa di moro / Roof copper-coloured
<b>Chemical composition:</b>	
Manganese (Mn)	0.9 – 1.5%
Magnesium (Mg)	0.2 – 0.8%
Iron (Fe)	0.7%
Silicon (Si)	0.5 - 0.6%
<b>Mechanical properties:</b>	
Traction resistance	150 – 200 MPa
Elongation	3 % min.
<b>Dimensional characteristics:</b>	
Standard thickness	0.8 – 1.0 mm
Tolerance	UNI EN 485-4
Standard widths	1000 - 1250 mm Further widths can be supplied on request
Coil weight	from Kg 100 to Kg 3000
<b>Employ:</b>	
Industrial and civil building, facades and roof covering	

MAZZONETTO S.P.A.